SPOTLIGHT: SPECIALISED VESSELS



# A new maintenance support vessel for Shell's smaller gas fields in the southern North Sea boasts a number of technological innovations, as **Russell McCulley** reports.

he Kroonborg vessel went to work this spring in the UK and Dutch sectors of the southern North Sea, where Shell's ONEgas business unit and the Shell-ExxonMobil joint venture NAM operate 56 gas producing platforms, 44 of them unmanned. The bespoke support vessel is a key piece of the company's operational strategy in the region, where production is shifting from mature, declining reservoirs to smaller gas deposits.

That strategy, put in place over the past several years, includes a significant reduction in the use of helicopters to transport maintenance crews, says ONEgas project leader Haije Stigter. The *Kroonborg* serves as both a "walkto-work" vessel and an efficient way to transport the equipment and chemicals needed to maintain gas production.

"The big reservoirs have been discovered and developed," says Stigter of the mature Southern North Sea basin. "But there are smaller accumulations waiting to be developed. So there are two drivers. With mature assets and declining reservoirs, we continuously need to look at managing our operating costs and field life. And with smaller, newer accumulations, we need to look at optimising our development costs."

About 15 years ago, Shell began moving to marine access-only

facilities to cut both operating expenses at mature fields and the cost of exploring new, smaller discoveries. The shift to "minimal facilities" had the "knock-on effect of not having to put a helideck and all the associated equipment on the platform", Stigter says.

The first platforms introduced under the walk-to-work scheme were designed to be visited by "small, fast rescue-type craft, where we could put six people on the platform in quite moderate sea states. And since 2006, we've used motion compensated gangways, initially fitted onto the backs of standard DP-2 platform supply vessels."

The new approach worked well

enough, but operations were hampered by inclement weather and sea states. Cranes on the small vessels could not operate when waves exceeded about 1.5 metres, which meant work was mostly limited to the warmer months. Restricted space also made it difficult to transport the significant amount of chemicals needed to maintain production, such as corrosion and hydrate inhibitors.

In 2012, Shell engineers started to toss around ideas for a new service and supply vessel to meet multiple needs. Those early meetings started with a fundamental question, Stigter recalls.

"If we had a blank piece



EASY COMMUTE: The Kroonborg vessel was designed to fit Shell's walk-towork strategy for its smaller southern North Sea gas fields.

of paper, what would a total solution for our ONEgas operations look like? We not only want to be able to put people on the platform, we also want to put materials on the platform. And wouldn't it be nice to be able to transport the chemicals we need to produce and evacuate wet gas?"

### **Riding the waves**

The *Kroonborg* vessel ticked the right boxes on Shell's wish-list. Measuring 80 metres in length and almost 16 metres in width, the ship has accommodations for up to 60 people, including a crew of 20. Built by Royal Niestern Sander shipyard for owner and operator Royal Wagenborg, the vessel is chartered to Shell for an initial period of 10 years.

The ship sports a fully integrated 22-metre Amplemann gangway that compensates the motion of waves up to 2.5 metres. More unusual is the vessel's motion compensating crane, said to be the first of its kind (see page 21).

"When we signed the contract in 2013, we requested a motion compensated crane on the vessel, but that didn't exist then," Stigter says. As it happens, another Dutch company, Barge Master, was conducting field trials at the time on a motion compensation system that could be configured to work with a large crane. The equipment was much larger than what Shell needed, or what the *Kroonborg's* limited deck space could accommodate.

"It's interesting — you put a demand out into the market, and there will be a company out there to pick up the challenge and start developing a solution," Stigter says. "We found a partner in that respect with Barge Master, which already worked with motion compensation but put all of its technology and knowledge into this motion compensated crane."

The Barge Master crane, as configured for the Kroonborg, can lift up to five tonnes 32 metres above sea level at a reach of up to 20 metres or 15 tonnes at a reach of 10 metres. "It's been working quite happily in threemetre seas," Stigter notes – all the more remarkable, he adds, "considering the fact that the crane didn't exist when we signed the contract in June, 2013, but was installed on the vessel late last year. And we've now had a few months working with the vessel, putting it through its paces, and everything works like a dream, within the boundary conditions that we set."

The motion compensation technology increases the weather window for offshore operations from about half of a typical year — the "workability" rate Shell was getting with the smaller vessels — to between 85% and 90%, based on historic metocean data, Stigter says.

The equipment is complemented by a propulsion system comprising two Voith Schneider Propellers and two Voith Inline Thrusters. The system provides the station keeping necessary to transfer personnel and materials safely, Stigter says, and to make use of the vessel's chemical supply and cold start-up capabilities. PG Marine Group, now known as PG Flow Solutions, provided the Kroonborg's cold start and inspection, repair and maintenance (IRM) package, a below-deck arrangement of pumps, injection and control systems, a nitrogen generator, umbilicals and hose reels. The below-deck tank installation, said to be the first of its type,



» frees up the 500-square metre deck space for other equipment.

The cold start system allows start-up of highpressure gas wells up to 425 bar by incorporating a heated monoethylene glycol unit. Without the heating capability, the gas pipelines are susceptible to the Joule-Thomson effect —the extreme cooling of high-pressure gas at start-up of production, which can make the steel brittle, Stigter points out.

### **Cleaner fuel**

In what Shell says is another first, the vessel runs on gas-to-liquids (GTL) fuel, which has made some inroads as a cleaner burning alternative to diesel onshore. Kroonborg, Stigter says, "represents the first commercial marine application of GTL in the world". Shell, Niestern Sander shipyard and Wagenborg collectively approached the vessel's engine manufacturer, PON Power, and the classification society Bureau Veritas to have the fuel approved for marine applications. "There's virtually no sulfur, no soot emissions," he says. "It's a much cleaner fuel."

Turbulent North Sea waters

called for a stable hull design for the walk-to-work vessel. While 33 of the 44 unmanned platforms operated by ONEgas have helidecks, they see little use these days.

"We're using walk-to-work at those locations too, because we can be at the facility at daybreak and leave the location at sunset," Stigter says. To get a sizeable crew to a platform by helicopter would require multiple trips each way. "With a helicopter, you get shorter days, fewer working hours."

Since it doubles as an accommodations unit, Shell requested that the vessel provide as much stability as possible.

"One of the design criteria was that it needed to provide comfort for people who work on the platforms but aren't necessarily seafarers," Stigter says. Niestern Sander worked with hull designer Conoship to develop a design that would work in conjunction with the Voith Schnieder propulsion system to minimise roll, noise and vibration.

While the company has no immediate plans to build



### "The vessel has been working quite happily in three-metre seas." Haije Stig

Haije Stigter, ONEgas

additional vessels like the *Kroonborg*, Stigter says the concept could be put to good use in other offshore areas.

"Our operations are not dissimilar to operations in the Gulf of Mexico or South-east Asia," he says. "I'd like to see a world where we don't fly people to platforms, for several reasons. You avoid the frustrations of the probability of not having people and materials on the same place at the same time, for

one. And moving people around with vessels is inherently safer than moving them around with helicopters."

## Lowering the swing load

utch technology company Barge Master was still testing its innovative BM-T700 modular motion compensating platform when Shell proposed the idea of a similar, but much smaller, piece of kit for the *Kroonborg* crane.

The BM-T700 consists of three hydraulic cylinders, arranged in a triangle, that work together to compensate heave, roll and pitch — the three of the six degrees of freedom that most affect lifting operations (dynamic positioning or anchoring systems compensate for the horizontal motions surge, sway and yaw). The platform has a payload capacity of 700 tonnes or can accommodate a crane with an average capacity of 160 tonnes at a radius of 12 metres.

The set-up requires considerable space - the platform and foundation together weigh 270 tonnes and the foundation has a footprint of 18 metres x 15 metres. Shell used the BM-T700 system earlier this year to install a permanent bridge between a new depletion compression platform and the existing gas production platform at the Malampaya field in the Philippines (see page 45). But putting a motion compensated crane on the Kroonborg required significant reengineering, says Barge Master chief executive Martijn Koppert.

"They said, 'we only need to lift five tonnes at a 20-metre



**CUSTOM CRANE:** The motion compensating BM-T40 crane went from the drawing board to ship's deck in just 18 months.

radius, but we don't have a lot of deck space'," Koppert recalls of the initial talks with Shell in late 2012. The company wanted the set-up scaled down to a footprint that would not exceed four metres by five metres. "We said, 'we can make the T700, this triangular platform, a bit smaller. But we will never get to the footprint that you have in mind'. So we had to go back to the drawing board."

Barge Master redesigned the platform "to a more sequential set-up", Koppert says, with two cylinders compensating for roll and pitch to keep the pedestal upright, then one cylinder compensating for heave. "The T700 has many applications, but we had to incorporate that technology into a design specific to a crane, and drastically reduce the footprint. The bigger the area, the better — it was very difficult to concentrate in a small footprint."

Nevertheless, the company was able to design, test and deliver the BM-T40 system for the *Kroonborg* in about 18 months.

"This is the first fully motion compensated crane on the market," Koppert says.

The crane enables the *Kroonborg* to work in close proximity to platforms, in wave heights up to three metres.

"I worked a lot offshore, and



### "This is the first fully motion compensated crane on the market."

Martijn Koppert, Barge Master

often experienced the problem of swinging load," he says. "A heave compensated crane does not eliminate swinging. That's why we came up with the concept of the motion compensated crane."

The technology creates a much wider operating window and increases safety, "and by doing that, you reduce cost tremendously", he says. "The one thing crane operators have to get used to is, when they're sitting in the crane, they're sitting still but the vessel is moving. That's a bit of a strange experience, but they get used to it. Even the guys who normally get seasick can operate this crane."

### Secure your stand



Your platform for the future

EXHIBITION & CONFERENCE 13 & 14 OCTOBER 2015



### AMSTERDAM THE NETHERLANDS

I amsterdam.

🙏 n a v i n g o

KVIR Stay in touch